

## ARTICULATING FAR FOCUS VIDEO BORESCOPE



Full-Color, IPS Anti-Glare LCD Display

High-Capacity SD Storage and USB Connectivity

Joystick-Controlled, 360° Camera Articulation

Video Start-Stop

Ergonomic Pistol Grip Design

IP 54 Base Unit

Rechargeable Li-ion Battery 4 Hour Runtime

On-Board Image Processing

4X Digital Zoom

Image Capture Trigger

Tungsten Braided IP 67 Insertion Tube


60,000 Lux, 6-Stage LED Illumination



**6.0  
mm**

**6.0mm DIAMETER**

Available in a length of 1.5m and 3.0m. The Far Focus sees clearly beyond the normally short focal distances of standard industrial borescopes. Featuring 4-layer Tungsten sheathing for smooth entry and exit, and are IP 67 rated for rugged durability.

**ULTRA-PORTABLE DESIGN**

No need for a separate monitor. Our lightweight, compact design has a built-in, full-color LCD display. All image capture, storage and processing is handled within the standalone unit, and the rechargeable Li-ion battery delivers up to 4 hours of cord-free run time.

**DIRECT RESPONSE ARTICULATION**

Designed for responsiveness and accuracy, the direct mechanical articulation never requires calibration, and the camera/LED module stays in place even when your thumb is removed from the joystick.

**UNRIVALED SERVICE AND EXPERTISE**

The VJ-3 is brought to you by the same team of borescope experts that changed the industry 10 years ago with the world's 1st mechanically articulating, joystick-controlled video borescope. Find out why we are still the #1 seller of borescopes in the US.

<b>INSERTION TUBE</b>	Outer Diameter	6.0mm
	Length	1.5m and 3.0m
	Exterior Material	Tungsten EasyGlide, crush-resistant
	Chemical Compatibility	Water, machine oil, heating oil, diesel, 3.5% saline concentrate
	Articulation Range	360° around, 160±10° backward
<b>OPTICS</b>	Field of View	100° x 75°
	Depth of Field	.5 inches - ∞
	Effective Pixels	450,000 pixels
	Illumination Method	6 Super high-intensity white LEDs
	Illumination Output	≤ 60,000lux (3x brighter than standard VJ-3)
<b>BASE UNIT</b>	Display Monitor	3.5" IPS anti-glare LCD, 640*480 resolution
	Articulation Control	Thumb-actuated, mechanical rocker
	Joystick Lock	Automatic
	Brightness Control	6-step LED brightness adjustment
	Control Buttons	Image capture, video capture, LED control, frame rotation, freeze frame, 4X zoom, menu access / navigation
	Playback	Photos, videos (w/wo audio), thumbnail view
	Audio / Microphone	3.5mm headset / microphone jack
	Internal storage	16GB SD Card / 10,000 photos or 8 hours video
	Data I/O ports	SD card, micro USB, TV Out (NTCS / PAL) or HDMI
	Battery	One 18650B PCB-Protected Li-ion battery (replaceable)
	AC Power (optional)	100V - 240V
	Operating Method	One handed, portable
	Dimensions	13.0" x 12.0" x 4.5"
Weight	2.2 lbs. / 1.0 kg	
<b>MENU FUNCTIONS AND OPTIONS</b>	User Interface	Drop down operating menu
	File Management	Photo and video recording, playback, thumbnail preview, delete
	Image Control	Image rotation, live freeze, zoom in/out
	Image Format	JPEG, optional date and time stamp
	Video Format	AVI, optional date and time stamp
	Language	English, Spanish
<b>OPERATING LIMITS</b>	Run Time	≤ 4 Hours
	Operating Temp. Base Unit	-20 – 50°C, -5 – 120°F
	Operating Temp. Insertion Tube	-10 – 50°C, 15 – 120°F
	IP Rating, Insertion Tube	IP67
	IP Rating, Base Unit	IP54